

		16-20	0.5 max	Sasol Wax GmbH
Tekniwax 512	56-64	32 typ		Sasol Wax (South Africa) (Pty) Ltd.
R 7346	*60-63	15 max	0.5 max	Sasol Wax Americas
R 7352	*64-67	14 max	0.5 max	Sasol Wax Americas
Präzisionsgusswachse				
R 2542	*60-63	9-15	0.4 max	Sasol Wax Americas
M 1085	*79 min	17 typ	2 max	Sasol Wax Americas
C 80	77-83	7 max	0.75 max	Sasol Wax (South Africa) (Pty) Ltd
H 1	96-100	1 max 1	< 0.1 typ	Sasol Wax

				(South Africa) (Pty) Ltd
Düngemittel Konditionierer				
6114	33-39			Sasol Wax GmbH
3499	30-45			Sasol Wax GmbH
Diamant Industrie				
Collector DB	56-63	68-72 (Kegelpenetration) (ASTM D 1321)	40 typ	Sasol Wax (South Africa) (Pty) Ltd.
Konditionierung von Pferderennbahnen				
Tekniwax 201	64-74	30-42 (Kegelpenetration) (ASTM D 1321)	40 typ	Sasol Wax (South Africa) (Pty) Ltd
Teppich Rücken				
HydroWax® 652	Wassergehalt 54% typ.	pH 9 typ	Emulgator kationisch	Sasol Wax (South Africa) (Pty) Ltd
HydroWax® RV	Wassergehalt 48-52	pH 7.5 typ	Emulgator anionisch/ säure - stabil	Sasol Wax GmbH

*ASTM D

Diese Produktinformation ist lediglich ein Hinweis und beinhaltet keinerlei Garantie

The content on this Sasol Wax web site is proprietary to Sasol Wax and only for general information and use. In particular the content does not constitute any form of legal or others advice, recommendation or arrangement by Sasol Wax (which includes its divisions, affiliates, joint ventures or departments) or its associated information providers, and is not intended to be relied upon by users in making (or refraining from making) any specific investment or other decisions. Appropriate expert advice should be obtained before making any such decision or using the information for any specific purpose.